



P10R

All-In-One Industrial Panel PC

- Equipped with 4-core ARM architecture A55 processor
- Wide voltage and temperature working performance
- Support 802.11a/b/g/n/ac protocol, dual Wi-Fi antennas and Bluetooth 5.0
- 10.1-inch flat capacitive touch panel is impact-resistant
- Rich interfaces, including multiple USB/RS232/LAN/HDMI and other I/O ports
- Designed with a mini PCIe slot for communication module or SSD expansion



- Durability**
- Front Panel IP65 compliant
 - ±8kV contact discharge, ±15kV air discharge

- Operating System**
- Android 12

- Processor**
- RK3568
(up to 2.0GHz,4 cores)

- Graphics**
- Mali-G52-2EE

- Memory**
- 4GB LPDDR4x on board

- Storage**
- 64GB eMMC

- Display**
- 10.1", HD (800x1280), 700 Nits
 - 10 point capacitive touch screen

- Audio**
- Optional 2W speaker

- Keyboard & Input**
- Power key x1

- Network & Connectivity**
- Intel® Wi-Fi 5 RTL8822CS (802.11 ac)
 - Bluetooth® V5.0
 - Optional 4G LTE
LTE-FDD: B1/3/5/7/8/20
LTE-TDD: B40
WCDMA: B1/5/8
GSM: 900/1800
China (China Unicom, China Telecom, China Mobile),
Europe, Middle East, Africa, Taiwan, Japan

- I/O Interface**
- Micro SD card x 1
 - SIM card x 1
 - USB3.0 (typeA) x 1
 - USB3.0 OTG (typeA) x 1
 - USB2.0 (typeA) x 2
 - 3.5mm AudioJack x 1
 - HDMI 2.0 typeA x 1
 - 10/100/1000 Ethernet (RJ45) x 1
 - Serial port (RS232: D-sub, 9-pin) x 2
Optional RS232 x 1/RS485 x 1
 - DC5.5mm-In jack x 1 (support 12-24V)
 - SMA x 2

- Battery**
- 100-240V, 50Hz-60Hz, 48W

- & Charging**
- Separated 3V/220mAh RTC

- Environment**
- Operating temperature: -20°C to 60°C (-4°F~140°F)
 - Storage temperature: -30°C to 70°C (-22°F~158°F)
 - Humidity: 95% Non-Condensing

- Dimension**
- 257.2 mm (L) × 170 mm (W) × 45.95 mm (H)

- Weight**
- 1.2 kg

- Accessories**
- Standard: Adapter, Hook Assembly, Antenna

- Warranty**
- One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Adapter



Hook Assembly



Antenna (wifi)

Optional



Antenna (4G)

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)

Tel: (+86) 400-830-4882

Email: inquiry@onerugged.com

Web: www.onerugged.com

Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen

